

Safety Data Sheet

Approval/Revision date: 11.02.2010
Print Date: 23.09.2010
00000024678/Version: 1.4
Page: 1/6



1. Identification of the substance/preparation and of the company/undertaking

Product name: 550R Violet Plate Replenisher

Product code: 9321100

Supplier: KODAK LIMITED, Hemel One, Boundary Way, Hemel Hempstead, HP2 7YU, Great Britain

IN EMERGENCY, telephone: 0870-2430270. Available during office hours only.

For further information about this product, telephone 0870-2430270 or email kes@kodak.com.

Synonyms: None.

Product Use: plate processing chemical (developer), For industrial use only.

2. Hazards identification

This Safety Data Sheet conforms to REACH Regulation (EC) 1907/2006.

Product: Irritant. Irritating to eyes and skin.

3. Composition/information on ingredients

Weight %	Component	CAS-No.	EINECS-No./ ELINCS No.	Classification
1 - 5	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., inner salts	61789-40-0		Xi; R36**
0.5 - < 3	Potassium hydroxide	1310-58-3	215-181-3	C; R22, R35*
0.1 - < 1	Polydimethylsiloxane	9016-00-6		**

* Symbol and R Phrase according to EC Annex I

** Substance not listed in EC Annex I

4. First aid measures

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms occur.

Eyes: In case of contact with eyes, flush immediately with plenty of water and seek medical attention.

Skin: Immediately flush with plenty of water for at least 15 minutes and wash using soap. Get medical attention if symptoms occur.

Ingestion: Do NOT induce vomiting. Give victim a glass of water. Get medical attention immediately. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Extinguishing Media: Use appropriate agent for adjacent fire.

Safety Data Sheet

Approval/Revision date: 11.02.2010

Print Date: 23.09.2010

000000024678/Version: 1.4

Page: 2/6

Special Fire-Fighting Procedures: No special fire fighting procedure is necessary.

Hazardous Combustion Products: None

Unusual Fire and Explosion Hazards: None.

6. Accidental release measures

Personal precautions: See Section 8 for recommendations on the use of personal protective equipment.

Environmental precautions: Prevent spillage from entering drains. Absorb spill with vermiculite or other inert absorbant material such as sand or earth, then place in a suitable container for proper disposal. Clean surface thoroughly with water to remove residual contamination.

Waste disposal: Contaminated absorbent should be disposed of in accordance with local regulations.

7. Handling and storage

Personal precautions: Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Use with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: No special precautionary measures should be needed under anticipated conditions of use.

Storage: Cool conditions (5 - 30°C). Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

Ventilation: Match ventilation rates to conditions of use so as not to exceed any applicable exposure limits (see Section 8). Good general ventilation of 10 or more room volumes per hour in the work area is recommended.

8. Exposure controls/personal protection

Occupational exposure controls: Not established

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions.

Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment.

Eye protection: Wear safety glasses with side shields or protective goggles whenever mixing or handling solutions.

Skin and body protection: Using the information provided in Section 2, seek the advice of the glove supplier as to the most suitable glove material. Avoid skin contact when mixing or handling the substance/preparation or a mixture by wearing impervious gloves and protective clothing appropriate to the risk of exposure.

Use chemical resistant gloves. In case of prolonged immersion or frequently repeated contact:

Material	Thickness	Breakthrough time
Nitrile rubber	>= 0.38 mm	> 480 min
Neoprene	>= 0.65 mm	> 240 min
butyl-rubber	>= 0.36 mm	> 480 min

Safety Data Sheet

Approval/Revision date: 11.02.2010
Print Date: 23.09.2010
00000024678/Version: 1.4
Page: 3/6

Avoid natural rubber gloves.

The protective gloves to be used must comply with the specifications of the EC directive 89/686/EEC and the resultant standard EN 374. This recommendation applies only to the product stated in the Safety Data Sheet and supplied by us as well as to the purpose specified by us.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and chemical properties

Physical form: liquid

Colour: light yellow

Odour: odourless

Specific gravity: 1.0081

Vapour pressure: 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 95 - 100 %

Boiling point/boiling range: > 100 °C (212.0 °F)

Water solubility: completely soluble

pH: 13

Flash point: does not flash

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Strong acids, Metals.

Hazardous decomposition products: None under normal conditions of use.

Hazardous Polymerization: Hazardous polymerisation does not occur.

11. Toxicological information

Effects of Exposure

Inhalation: Expected to be a low hazard for recommended handling.

Eyes: Irritating to eyes.

Skin: Irritating to skin.

Ingestion: Expected to be a low ingestion hazard.

Safety Data Sheet

Approval/Revision date: 11.02.2010
Print Date: 23.09.2010
00000024678/Version: 1.4
Page: 4/6

Data for Potassium hydroxide (CAS 1310-58-3):

Acute Toxicity Data:

Oral LD50 (rat): 273 mg/kg

- Skin irritation: severe

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Toxicity to fish (LC50): > 100 mg/l

Toxicity to daphnia (EC50): > 100 mg/l

Persistence and degradability: Readily biodegradable.

13. Disposal considerations

This information is provided to assist users in the correct disposal of working solutions prepared and used to Kodak specifications.

Waste material: Waste material is currently classified as hazardous under Council Directive 91/689/EEC. The European Waste Catalogue Code is 09 01 02 Water based offset plate developer solutions. Dispose according to the local regulations or guidelines that apply to the category of waste. Ensure the use of properly authorised waste management companies.

Product containers: If thoroughly cleaned, preferably by rinsing at least three times with small quantities of water, waste product packaging may be consigned for recovery or disposal as non hazardous waste. Whenever possible, minimize waste by using the rinsing water to make up the working solution. The European Waste Catalogue Code is 15 01 02 plastic packaging.

Waste product packaging contaminated by residues of hazardous contents should be consigned for disposal as hazardous waste. In this case, the European Waste Catalogue Code is 15 01 10 packaging containing residues of or contaminated by dangerous substances.

14. Transport information

The information given below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions. Please consult the product packaging for further details.

ADR:

UN-Number:	UN1814
Proper shipping name:	POTASSIUM HYDROXIDE SOLUTION
Class:	8
Packaging group:	III

IATA:

UN-Number:	UN1814
Proper shipping name:	POTASSIUM HYDROXIDE, SOLUTION
Class:	8
Packaging group:	III

Safety Data Sheet

Approval/Revision date: 11.02.2010

Print Date: 23.09.2010

00000024678/Version: 1.4

Page: 5/6

IMDG:	UN-Number:	UN1814
	Proper shipping name:	POTASSIUM HYDROXIDE SOLUTION
	Class:	8
	Packaging group:	III
RID:	UN-Number:	UN1814
	Proper shipping name:	POTASSIUM HYDROXIDE SOLUTION
	Class:	8
	Packaging group:	III

For more transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

Notification status

Regulatory List	Notification status
TSCA	Not all listed
DSL	Not all listed
NDSL	None listed
EINECS	Not all listed
ELINCS	None listed
NLP	None listed
AICS	Not all listed
IECS	Not all listed
ENCS	Not all listed
ECI	Not all listed
NZIoC	Not all listed
PICCS	Not all listed

"Not all listed" indicates one or more component is either not on the public Inventory or is subject to exemption requirements. If additional information is needed contact Kodak.

Labelling:

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

Contains: 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., inner salts , Potassium hydroxide

pH: > 12

Safety Data Sheet

Approval/Revision date: 11.02.2010
Print Date: 23.09.2010
000000024678/Version: 1.4
Page: 6/6



Symbol/Indication of Danger: Xi: Irritant

Risk Phrases: R36/38: Irritating to eyes and skin.

16. Other information

The following is an explanation of the meaning of the Symbol letters and Risk Phrases for the pure substance(s) referred to in Section 2 of this Safety Data Sheet.

C: Corrosive
Xi: Irritant

R22: Harmful if swallowed.
R35: Causes severe burns.
R36: Irritating to eyes.

Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.
